

## 9415

#### 9410L + SAFETY = 9415

# Everything that's great about the 9410L LED Lantern, plus safety certifications

At just 3 pounds and 413\* lumens, the new 9415 LED Lantern packs the power without the weight. Four LEDs, powered by the latest generation Ni-MH batteries illuminate a distance of 360 yards (325\* meters). And it's loaded with innovative technology and features you have come to expect from Pelican.

Safety approved for the most volatile work areas, the 9415 LED Lantern is safe and one of the most compact, high output lanterns on the market.

9415 LED Lantern: Lightweight, big LED performance you can trust.

- \*Performance data is to FL 1 standards
- Built Pelican tough
- Super bright LED beam
- Safety Certified Class I, Division I
- Handy push button on/off switch
- High/Low/Flashing Modes



#### **MATERIALS**

Body ABS O-Ring EPDM

Lens Polycarbonate (PC)

Shroud EXL

## **COLORS**

High Visibility Yellow

## **LIGHT SPECS**

Lamp Type LED

#### **POWER**

Battery SizeCBattery TypeNiMHBattery Quantity4Batteries Includedyes

Charge Time 5 hrs 30 mins
Battery Level Indicator RGB LED
Volts 4.8v

## WEIGHT

Weight With Batteries 49.3 oz (1398 gr)
Weight Without Batteries 0.0 oz (0 gr)

## **SWITCH**

Switch Type Push Button

**Light Modes** High / Low / Flashing

#### **CERTIFICATIONS**

Class I, Division 1

## **OTHER**

Minimum Pack 1
Package Code B

FL1 STANDARD	HIGH	LOW
314	413 LUMENS	159 LUMENS
0	4h 30mins	12h 0mins
	325m	201m
	26352cd	10076cd
	IPX4	

## **ACCESSORIES**



**9413DL** Diffuser Lens



9416 Deck/Dash Charger Base Unit



**6057F** 110V Transformer (USA)



**6061F**Direct Wiring Rig for Fast Charger



**8056F** 12v Plug-in for Fast Charger



9418 Replacement Battery



**6058A** 220V Transformer (Australia)

## Pelican