Designed + Manufactured in the USA



January 2018

olosion Proof LED Tank/Area Light

The BRICK® Accessories **Product Protection, Light Dispersement, Multi-functional Options**



Blast Shield

Resin Case



Roll Top Anti-Glare Diffuser



High Dome Diffuser



The Body Wrap



Paint Overspray Protection Bags (50 pack) Replacement Blast Shields (12 Pack)



Various Cord Lengths & Plug Options Available (shown w/ NATO Plug Option)

Product Features

- ▶ Approved for: Class I, Div 1 & 2, Group C & D
- ▶ Approved for: Class II, Div 1 & 2, Group E, F, & G
- ▶ **Approved for:** CSA Zones 1 & 2; Zones 20, 21, & 22
- ▶ Conforms to: UL Stds 153, 781, 844;
- ▶ Certified to: CSA Stds C22.2#s 12, 25, 137
- Suitable for Wet Location Use
- ► Certified: Portable Luminary (Portable Luminaire)
- ► Temperature Rating: T-code: T5 (-20°C to +40°C); T4 (-20°C to +100°C)
- ▶ **LED Color:** ~6000K, CRI >70
- ▶ Rated with optics: 50,000 lux at 1'
- ▶ Rated with optics: >11,700 lumens
- ► Reflective Optic Beam Angle: 60°
- ► Light Head Power: 36 VDC, 2-3A (A&C Models) | 120-240VAC, 2.2-1.2A (B Model)
- ▶ Weight: 10 lbs (light head only)
- ▶ Dimensions: 10"L x 5"W x 4"H
- ▶ Protection: Polyurethane Bumper
- ► Accessories: Blast Shields, Dome Diffusers, Body Wrap, etc... (See Above)
- Multiple Mounting Options: Mechanical/Magnetic mounting (See Back)















MULTIPLE MOUNTING OPTIONS

The BRICK® is designed with mounting plates on four sides of the light body to facilitate versatile magnetic or mechanical mounting and connection options specifically engineered for this light.







Western Technology, Inc. 3517 Arsenal Way Bremerton, WA 98312 Fax: (360) 917-0083

Toll Free: (800) 654-5483 Local: (360) 917-0080