

9455

Introducing the Pelican 9455 RALS, the world's first Class I Division 1, ATEX Zone 0 and IECEx ia safety certified remote area light. Now you can take remote area lighting to hazardous areas around the globe.

The 125° beam angle along with up to 1,600 lumens and providing up to 10 hours of run time, the 9455 will support full work shifts and deliver safe situational awareness. Weighing only 16 pounds and completely collapsible, makes for easy carry and quick set ups. The dual light modes, High/Low provide flexible options and is equipped with a 30 minute visible low battery warning indicator.

From confined spaces to tight manholes, nothing stops the Pelican 9455 RALS from illuminating the work site, safely.

**The repair of the 9455 needs to be conducted by a certified Pelican Products repair center due to the requirements of the safety certificate.

- Class I Division 1, ATEX Zone 0, IECEx ia safety certified
- Up to 1,600 lumens
- Up to 10 hours run time
- NiMH rechargeable battery
- · High / Low lighting modes
- · Low battery indicator
- Hi Vis safety yellow
- Visit our 9455 explore page for more information



DIMENSIONS

Head (L x W x D) 8.26 x 5.71" x 1.97 (21 x 14.5 x 5 cm)
Closed (L x W x D) 15.35 x 7.87" x 9.06 (39 x 20 x 23 cm)

Light Head Height (max) 31.50" (80 cm)

Cord Length 12.60" (32 cm)

MATERIALS

Body Polycarbonate (PC) / ABS

Head Aluminum

Lens Polycarbonate (PC)

COLORS

High Visibility Yellow

LIGHT SPECS

Lumens (High)1600Lumens (Low)800Lamp TypeLEDNumber of LEDs10Lamp Life50000

Lamp Life50000 hrsBeam Spread125°IP Rating54

POWER

Run Time (High) 5.00 hrs
Run Time (Low) 10.00 hrs
Battery Type NiMH
Battery Lifespan 300 cycles
Charge Time 8 hrs

Battery Level Indicator Low battery warning

 Watts
 21 W

 Volts
 10.8v

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

WEIGHT <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Weight 16.00 lbs (7.3 kg)

Document created on 11-07-18

SWITCH

Switch TypeSilicone Rubber KeypadLight ModesHigh / Low / Flashing

CERTIFICATIONS

IECEx ia

Class I, Division 1 ATEX Zone 0

ACCESSORIES