Meets The New BPI I200 Standard

SENSIT[®]GOLD

000000

SENSIT® GOLD EXCO+1200

The revised BPI 1200 Standard for residential energy audits and testing requires:

- ✓ Digital Display for LEL
- ✓ Audible Tick Rate
- Preset Alarms

SENSIT[®] GOLD EXCO+I200 can also be used as an OSHA-compliant confined space monitor.

As an investigative tool, the LEL sensor is designed to find the source of combustible gas leaks fast.

Applications

- Combustible Gas Leak Detection
- Carbon Monoxide Investigations
- Confined Space Monitoring
- Combustible Gas Measurements
- BPI 1200 Energy Audits

You can depend on the **SENSIT**® **GOLD** EXCO+I200 to provide the safety and accuracy you need.

- ✓ 0 to 2000 ppm CO Readings✓ Calculate and Display CO Air Free
- ✓ UL 913 Certification

Displays 3 Gases

- LEL (Combustibles)
- Oxygen
- Carbon Monoxide (PPM)
- Air Free CO Readings (CF)

Standard Features

- UI 913 Certified
- Audible Tick Leak Detection
- Lowest Cost, Long Life Sensors
- Internal Pump
- Water/Dust Filter
- Field Calibration
- Calibration Alert
- Session Log
- Calibration Memory
- Infrared Download
- Audible/Visual Alarms
- Bright LCD Display
- Programmable Auto Shut Off

SENSIT[®] GOLD EXCO+I200

PRODUCT FEATURES

- 1 LUER PROBE CONNECTOR
- 2 SENSOR CAP
- 3 LEL / PPM SENSOR
- 4 INFRARED COMMUNICATIONS
- 5 BACKLIT LCD DISPLAY
- 6 ALARM LEDS7 OPERATION BUTTONS
- 8 TICK ADJUST
- 9 FLEXIBLE GOOSENECK
- 10 BATTERY COMPARTMENT

PRODUCT SPECIFICATIONS

 Size:
 11.5" x 3" x 2.32" (29.2 x 7.6 x 6.9 cm)

 Weight:
 1.2 lb. (0.5 kg)

 Operational Temp:
 -4 to 122 F (-20 to 50° C)

 Battery Life:
 Alkaline: Approximately 12 hrs. Continuous





SENSOR SPECIFICATIONS

TYPE LEAK (UL) LEL O2 CO **RESOLUTION** N/A 0.1% up to 2.0% 0.1% 1 ppm

RANGE
10-50,000 ppn
0-100% LEL
0-25%
0-2000 ppm

ACCURACY N/A ±10%

±0.2% or 10%** ±5 ppm or 5%**

**Whichever is greater



851 Transport Drive Valparaiso, IN 46383-8432

Phone: 888 4SENSIT 888 473 6748 219 465 2700

Fax: 219 465 2701 www.gasleaksensors.com MADE IN THE USA

SENSIT Technologies is in compliance with ISO 9001:2008





0.0/1

SENSIT"GOLD

2

3

4

5

6

7

8

9

10