## WATER PUMPS



## Rugged Design for Tough Jobs

CP hydraulic submersible pumps are so tough, it takes much more than stones and debris to stop them. They're designed for continuous pumping of water on building sites, in flooded excavations and cellars, and in similar situations.

These rugged pumps are built to deliver impressive performance for their size and weight. The 2 in pump handles dirty water containing small stones and debris up to 10 mm. The 3 in CP submersible trash pump can handle stone and debris in the slurry up to 60 mm in diameter. Cooled and lubricated by the hydraulic oil, they can be left to run dry without damage.

HYDRAULIC SUBMERSIBLE WATER PUMPS WAP 2 WAP 3   Weight kg (lb) 11 (24) 13 (29)   Height mm (in) 345 (13.6) 450 (17.7)   Width mm (in) 225 (8.9) 300 (11.8)   Oil Flow I/min (gpm) 18 - 24 (5-6) 26-38 (7-10)   Working Pressure bar (psi) 100 (1.450) 140 (2.030)   Pump Head Maximum m (ft) 25 (82) 32 (105)   Pump Flow Maximum I/min (gpm) 840 (222) 1,920 (507)   Discharge 2" 3"   EHTMA Class C D   Solids Handling Up To mm (in) 10 (0.4) 60 (2.4)   Sound Power Level Guaranteed* 95 92   Sound Pressure Level* (ISO 11203) (Lp, r=1m) dB(A) 840 (1014 41 810			
Height mm (in) 345 (13.6) 450 (17.7)   Width mm (in) 225 (8.9) 300 (11.8)   Oil Flow l/min (gpm) 18–24 (5–6) 26–38 (7–10)   Working Pressure bar (psi) 100 (1.450) 140 (2.030)   Pump Head Maximum m (ft) 25 (82) 32 (105)   Pump Flow Maximum l/min (gpm) 840 (222) 1,920 (507)   Discharge 2" 3"   EHTMA Class C D   Solids Handling Up To mm (in) 10 (0.4) 60 (2.4)   Sound Power Level Guaranteed* 95 92   Sound Pressure Level* (ISO 11203) (Lp, r=1m) dB(A) 84 81		WAP 2	WAP 3
Width mm (in) 225 (8.9) 300 (11.8)   Oil Flow //min (gpm) 18–24 (5–6) 26–38 (7–10)   Working Pressure bar (psi) 100 (1.450) 140 (2.030)   Pump Head Maximum m (ft) 25 (82) 32 (105)   Pump Flow Maximum //min (gpm) 840 (222) 1,920 (507)   Discharge 2" 3"   EHTMA Class C D   Solids Handling Up To mm (in) 10 (0.4) 60 (2.4)   Sound Power Level Guaranteed* 95 92   Sound Pressure Level* (ISO 11203) (Lp, r=1m) dB(A) 84 81	Weight kg (lb)	11 (24)	13 (29)
Oil Flow l/min (gpm) 18–24 (5–6) 26–38 (7–10)   Working Pressure bar (psi) 100 (1,450) 140 (2,030)   Pump Head Maximum m (ft) 25 (82) 32 (105)   Pump Flow Maximum l/min (gpm) 840 (222) 1,920 (507)   Discharge 2" 3"   EHTMA Class C D   Solids Handling Up To mm (in) 10 (0.4) 60 (2.4)   Sound Power Level Guaranteed* 95 92   Sound Pressure Level* (ISO 11203) (Lp, r=1m) dB(A) 84 81	Height mm (in)	345 (13.6)	450 (17.7)
Working Pressure bar (psi) 100 (1,450) 140 (2,030)   Pump Head Maximum m (ft) 25 (82) 32 (105)   Pump Flow Maximum l/min (gpm) 840 (222) 1,920 (507)   Discharge 2" 3"   EHTMA Class C D   Solids Handling Up To mm (in) 10 (0.4) 60 (2.4)   Sound Power Level Guaranteed* 95 92   Sound Pressure Level* (ISO 11203) (Lp, r=1m) dB(A) 84 81	Width mm (in)	225 (8.9)	300 (11.8)
Pump Head Maximum m (ft) 25 (82) 32 (105)   Pump Flow Maximum l/min (gpm) 840 (222) 1,920 (507)   Discharge 2" 3"   EHTMA Class C D   Solids Handling Up To mm (in) 10 (0.4) 60 (2.4)   Sound Power Level Guaranteed* 95 92   Sound Pressure Level* 84 81	Oil Flow I/min (gpm)	18–24 (5–6)	26-38 (7-10)
Pump Flow Maximum I/min (gpm) 840 (222) 1,920 (507)   Discharge 2" 3"   EHTMA Class C D   Solids Handling Up To mm (in) 10 (0.4) 60 (2.4)   Sound Power Level Guaranteed* 95 92   Sound Pressure Level* 84 81	Working Pressure bar (psi)	100 (1,450)	140 (2,030)
Discharge 2" 3"   EHTMA Class C D   Solids Handling Up To mm (in) 10 (0.4) 60 (2.4)   Sound Power Level Guaranteed* 95 92   Sound Pressure Level* 84 81	Pump Head Maximum m (ft)	25 (82)	32 (105)
EHTMA Class C D   Solids Handling Up To mm (in) 10 (0.4) 60 (2.4)   Sound Power Level Guaranteed* 95 92   Sound Pressure Level* 84 81	Pump Flow Maximum I/min (gpm)	840 (222)	1,920 (507)
Solids Handling Up To mm (in) 10 (0.4) 60 (2.4)   Sound Power Level Guaranteed* (2000/14EC) Lw dB(A) 95 92   Sound Pressure Level* (ISO 11203) (Lp, r=1m) dB(A) 84 81	Discharge	2"	3"
Sound Power Level Guaranteed* 95 92   (2000/14EC) Lw dB(A) 95 92   Sound Pressure Level* 84 81	EHTMA Class	С	D
(2000/14EC) Lw dB(A) 95 92   Sound Pressure Level* (ISO 11203) (Lp, r=1m) dB(A) 84 81	Solids Handling Up To mm (in)	10 (0.4)	60 (2.4)
(ISO 11203) (Lp, r=1m) dB(A) 84 81		95	92
Part Number 1806 1014 41 1806 1014 42		84	81
	Part Number	1806 1014 41	1806 1014 42

\*Full details of measurement are available in the Safety and Operating Instruction of the product. It can be found on www.cpprintshop.com.



WAP 2



WAP 3